



Features

- Exclusive RS-1 Electronic Meter Initiated Controls
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Adjustable cycle times
- Calendar Day Override
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass (optional)
- Poly wound mineral tank with high flow 1" distribution tube
- High Flow brine safety float assembly, overflow fitting, grid plate, and brine well
- Space-saving, attractive, one-piece design

General Specifications	CD24	CD32
Grains Capacity / Lbs Salt Used* per regeneration	24,000 / 12 20,250 / 7.5 15,000 / 4.5	32,000 / 15 27,000 / 9 20,000 / 6
Maximum Raw Water Hardness (grains)	50	75
Maximum Clear Iron / Manganese (ppm)	3	5
Exchange Resin (cu ft)	.75	1.0
Mineral Tank (polyglass)	9 x 35	9 x 35
Brine Tank (polyethylene w grid & safety)	N/A	N/A
Service Flow Rate** (gpm)	8.0	11.0
Backwash Flow Rate (gpm)	1.5	1.5
Gallons Used / Regeneration	79	80
Space Required	23x14x 45	23x14x45
Approximate Shipping Weight (lbs)	88	100

* Factory Salt Setting: 15 lbs / cu. ft.

** The pressure drop does not exceed 15.0 psi at the service flow rate.

