



Features

- Eliminates Hardness (Calcium & Magnesium)
- Exclusive RS-1 Electronic meter initiated controls
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- Calendar Day Override
- Proprietary two valve bypass with 1" MNPT Connections
- High Flow 1" distributor
- Treated Water Refill with pre-brine option

General Specifications	CD24	CD32
Grains Capacity / Lbs Salt Used* per regeneration	24,000 / 12 20,000 / 7.5 15,000 / 4.5	32,000 / 15 27,000 / 9 20,000 / 6
Maximum Raw Water Hardness (grains)	50	75
Maximum Clear Iron / Manganese (ppm)	3	5
Exchange Resin (cu ft)	.75	1.0
Mineral Tank (polyglass)	9 x 35	9 x 35
Brine Tank (polyethylene w grid & safety)	N/A	N/A
Service Flow Rate** (gpm)	8.0	11.0
Backwash Flow Rate (gpm)	2.0	2.0
Gallons Used / Regeneration	79	80
Space Required	23x14x 45	23x14x45
Approximate Shipping Weight (lbs)	88	100

* Factory Salt Setting: 15 lbs / cu. ft.

** The pressure drop does not exceed 15.0 psi at the service flow rate.