



Features

- Eliminates Hardness (Calcium & Magnesium)
- Reduces Chlorine & Chloramine taste and odor
- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- Calendar Day Override
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- High Flow 1" distributor
- Mid-Vortech Standard
- Treated Water Refill with pre-brine option
- Standard brine tank size 18" X 33" with space saving 14" X 14" and oversized 18" X 40" brine tanks available
- High Flow brine safety float assembly, overflow fitting, grid plates and brine well

General Specifications	DSC32-3	DSC48-3
Grains Capacity / Lbs Salt Used* per regeneration	27,000 / 9.0	40,000 / 15.0
Catalytic Carbon Media	.5 cu ft	1 cu ft
Maximum Raw Water Hardness (gpg)	75	100
Maximum Raw Water Iron (ppm)	5	5
Service Flow Rate (gpm)*	5	8
Intermittent Flow Rate (gpm)	7	10
Backwash Flow Rate (gpm)	2.4	3.5
Mineral Tank Size (inches)	10 X 54	13 X 65
Gallons Used / Backwash	81	105
Space Required	18 x 28 x 62	18 x 31 x 73
Approximate Shipping Weight (lbs)	130	240

*The pressure drop does not exceed 15.0 psi at the service flow rate.