



Features

- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Includes meter to provide water usage history
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Adjustable Cycle Times
- High Backwash flow capability
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- High Flow 1" distributor
- Features Enpress® Vortech™ distributor plate
- Includes KMNO4 feed pot with grid platform and float shutoff
- Regenerates with KF02N potassium permanganate



General Specifications	G9I-3	G10I-3	G12I-3
Filter Media	Greensand Plus™		
Filter Media Capacity (cu ft)	1.00	1.50	2.00
Garnet Sand Underbed (lbs)	20	30	50
Mineral Tank (Vortech™)	9 x 48	10 x 54	12 x 52
Potassium Permanganate Solution Tank Size	10 x 16		
Removal Capacities Iron / Sulfur	10 ppm / 3 ppm	10 ppm / 3 ppm	10 ppm / 3 ppm
Service Flow Rate - Continuous (gpm)	4	5	6
Service Flow Rate - Intermittent (gpm)	6	7	8
Backwash Flow Rate (gpm)	5.0	5.0	6.0
Gallons Used / Regeneration	128	130	173
Space Required	9 x 21 x 57	10 x 22 x 62	13 x 24 x 60
Approximate Shipping Weight (lbs)	157	215	305