



## Features

- Treats Iron, Sulfur and Manganese
- Isobar II™ Series Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Adjustable cycle times
- Battery Back-Up
- High backwash flow capability
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass (optional)
- Poly wound mineral tank with high flow 1" distribution tube
- Features Enpress® Vortech™ distributor plate for exceptional backwashing capability
- Poly wound **10 X 54** AP Tank
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure

General Specifications	AF10	AF12	AF13	AF14
Filter Media Type	Smart Blend™			
Filter Media Capacity (cu ft)	1.5	2.0	2.5	3.0
<b>Provectr™</b> AP Tank (polyglass)	10 x 54	10 x 54	10 x 54	16 x 40
Mineral Tanks (Vortech)	10 x 54	12 x 52	13 x 54	13 x 65
Service Flow Rate - Continuous (gpm)	5	6	8	9
Service Flow Rate - Intermittent (gpm)	7	8	10	11
Backwash Flow Rate (gpm)	5.0	6.0	7.0	7.0
Gallons Used / Regeneration	100	120	140	140
Total Space Required Tank	10 X 20 X 68	13 X 23 X 68	13 X 23 X 68	13 X 30 X 73
Approximate Shipping Weight (lbs)	165	236	270	311

