



Features

- Isobar III Control Valve with meter for precise compressor control
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Designed for use with constant pressure (variable speed) and jet type pumping systems
- On demand meter for air compressor activation and data / history
- Quiet, high output, oil less air compressor for maximum aeration
- Adjustable Cycle Times
- High backwash flow capability
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Features Enpress® Vortech™ distributor plate



General Specifications	AF10AC-3	AF12AC-3	AF13AC-3	AF14AC-3
Filter Media Type	Smart Blend			
Filter Media Capacity (cu ft)	1.50	2.00	2.50	3.00
Provectr™ AP Tank (polyglass)	10 x 54	10 x 54	10 x 54	16 x 40
Mineral Tank (Vortech™)	10 x 54	12 x 52	13 x 54	13 x 65
Service Flow Rate - Continuous gpm	5	6	8	9
Service Flow Rate - Intermittent (gpm)	6	7	8	11
Backwash Flow Rate (gpm)	5.0	6.0	7.0	7.0
Gallons Used / Backwash	100	120	140	140
Total Space Required	10 X 20 X 68	13 X 23 X 68	13 X 23 X 68	16X30X73
Approximate Shipping Weight (lbs)	176	246	280	321

Note: Caution should always be used in sizing filters. Always choose a unit by satisfying the *Backwash Requirement*. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions. Oxyclean can be added to any existing Reactr or Reactr VS system.

