



Features

- Designed for use with constant pressure (variable speed) and jet type pumping systems
- Isobar II™ Series Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Quiet, high output, oil less air compressor for maximum aeration
- Adjustable cycle times
- Battery backup
- High backwash flow capability
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass (optional)
- Poly wound mineral tank with high flow 1" distribution tube
- Features Enpress® Vortech™ distributor plate for exceptional backwashing capability
- Poly wound 10 X 54 AP Tank
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure

General Specifications	AF10AC	AF12AC	AF13AC	AF14AC
Filter Media Type	Smart Blend			
Filter Media Capacity (cu ft)	1.50	2.00	2.50	3.00
Provectr™ AP Tank (polyglass)	10 x 54	10 x 54	10 x 54	16 x 40
Mineral Tank (Vortech™)	10 x 54	12 x 52	13 x 54	13 x 65
Service Flow Rate - Continuous (gpm)	5	6	8	9
Service Flow Rate - Intermittent (gpm)	6	7	8	11
Backwash Flow Rate (gpm)	5.0	6.0	7.0	7.0
Gallons Used / Backwash	100	120	140	140
Total Space Required	10 X 20 X 68	13 X 23 X 68	13 X 23 X 68	16X30X73
Approximate Shipping Weight (lbs)	176	246	280	321

Note: Caution should always be used in sizing filters. Always choose a unit by satisfying the *Backwash Requirement*. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions. Oxyclean can be added to any existing Reactr or Reactr VS system.

