



## Features

- Treats Iron, Sulfur and Manganese
- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- High backwash flow capability
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Features Enpress® Vortech™ distributor plate



| General Specifications                 | AF10-3       | AF12-3       | AF13-3       | AF14-3       |
|--|--------------|--------------|--------------|--------------|
| Filter Media Type                      | Smart Blend™ |              |              |              |
| Filter Media Capacity (cu ft)          | 1.5          | 2.0          | 2.5          | 3.0          |
| <b>Provectr™</b> AP Tank (polyglass)   | 10 x 54      | 10 x 54      | 10 x 54      | 16 x 40      |
| Mineral Tanks (Vortech)                | 10 x 54      | 12 x 52      | 13 x 54      | 13 x 65      |
| Service Flow Rate - Continuous (gpm)   | 5            | 6            | 8            | 9            |
| Service Flow Rate - Intermittent (gpm) | 7            | 8            | 10           | 11           |
| Backwash Flow Rate (gpm)               | 5.0          | 6.0          | 7.0          | 7.0          |
| Gallons Used / Regeneration            | 100          | 120          | 140          | 140          |
| Total Space Required Tank              | 10 X 10 X 62 | 10 X 12 X 62 | 10 X 13 X 62 | 16 X 16 X 73 |
| Approximate Shipping Weight (lbs)      | 165          | 236          | 270          | 311          |

