



Features

- Perfect for Filtering and Softening in ONE System
- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- Calendar Day Override
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- High Flow 1" distributor
- Features Enpress® Vortech™ mid-plate technology
- Treated Water Refill with pre-brine option
- Standard brine tank size 18" X 33" with space saving 14" X 14" and oversized 18" X 40" brine tanks available
- High Flow brine safety float assembly, overflow fitting, grid plates and brine well



| General Specifications | Two Tanks In One | |
|--|------------------|---------------|
| | DSF32LFMD-3 | DSF48LFMD-3 |
| Select Filter Media | 1 cu ft | 1.5 cu ft |
| Grains Capacity / Lbs Salt Used per regeneration | 32,000 / 15.0 | 48,000 / 24.0 |
| Service Flow Rate (gpm) | 5 | 8 |
| Intermittent Flow Rate (gpm) | 7 | 10 |
| Backwash Flow Rate (gpm) | 5 | 7 |
| Mineral Tank Size (inches) | 10 x 65 | 13 x 65 |
| Gallons Used / Backwash | 130 | 170 |
| Space Required | 18 x 28 x 73 | 18 x 31 x 73 |
| Approximate Shipping Weight (lbs) | 126 | 182 |

** The pressure drop does not exceed 15.0 psi at the service flow rate.