



## Features

- Perfect for Filtering and Softening in ONE System
- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- Calendar Day Override
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- High Flow 1" distributor
- Features Enpress® Vortech™ mid-plate technology
- Treated Water Refill with pre-brine option
- Standard brine tank size 16" X 33"
- High Flow brine safety float assembly, overflow fitting, grid plates and brine well



General Specifications	Two Tanks In One	
	DSF32LFMD-3	DSF48LFMD-3
Select Filter Media	1 cu ft	1.5 cu ft
Grains Capacity / Lbs Salt Used per regeneration	32,000 / 15.0	48,000 / 24.0
Service Flow Rate (gpm)	5	8
Intermittent Flow Rate (gpm)	7	10
Backwash Flow Rate (gpm)	5	7
Mineral Tank Size (inches)	10 x 65	13 x 54
Gallons Used / Backwash	145	185
Space Required	16 x 28 x 73	16 x 31 x 73
Approximate Shipping Weight (lbs)	126	182

\*\* The pressure drop does not exceed 15.0 psi at the service flow rate.